

Flat wagon Snps ⁵



General

Load Limits:

	A	B	C	D
S	36,7	44,7	52,7	62,7
120	0,00			

Tare:	ca. 27,3 t
R _{min} :	75 mm
Gauge:	TEN-RIV/G1
Axle load:	22,5 t
Ramp angle (R=150m):	2,5°
Loading area:	57,2 m ²
Load length:	22.000 mm
Load width:	2.640 mm
Height of floor (empty):	1.270 mm with sleepers: 1.340 mm

Running Gear

Y25Lsd1 (K)	
Wheel diameter:	920 mm
Wheel set type:	BA 004
Axle box type:	BA 182
Suspension:	coil spring

Brake

Brake type:	KE-GP-A 12"
Brake pads:	Cosid 810
Load braking:	MAX 59 t/contin., autom.
Handbrake (20 %):	operated from ground
Air reservoir:	100 l

Heavy single loads:

	m	—	t	±	mm
a-a	2,4	+	26,0		26,0
b-b	4,6	+	27,6		32,0
c-c	8,8	+	31,8		43,5
d-d	14,7	+	44,0		52,0
e-e	17,7	+	55,0		62,7
f-f	22,0	+	62,7		---

Draw gear and Buffer

Buffer Endkr/Hub:	Cat.A 590 kN/105 mm
Buffer plate dimensions:	340 x 550 mm
Draw gear:	normal/85 t

Equipment

28 fixed steel stanchions	
7 "Autonordic system" lashing straps	
36 fixed fastening bars outside at the framework	
10 folding sleepers:	70 mm
Wooden floor:	70 mm

Remarks

TSI

Load Goods

Steel and Wood products

Flachwagen Snps ⁵

Appendix to Data Sheet

